


THE RECOMMENDED MATING AUDIO PLUG IS 3.50mm 4-POLE PLUG



REV	ECN #	DESCRIPTION	DRAWING	APPROVED	DATE
A		NEW RELEASE	DEV1		2013/01/10

- NOTES :
- 1.0) RATING :
 - 1.1. VOLTAGE : 12 VDC (R.M.S.)
 - 1.2. CURRENT : 1 AMPERE MAXIMUM PER CONTACT AT 30° C T-RISE
 - 1.3. TEMPERATURE : -25° C TO +85° C
 - 2.0) ELECTRICAL CHARACTERISTIC
 - 2.1. CONTACT RESISTANCE : INITIAL 50m MAX. AFTER 100m
 - 2.2. INSULATION RESISTANCE : 100 M MIN.
 - 2.3. DIELECTIC WITHSTANDING VOLTAGE : 500 VAC AT SEA LEVEL
 - 3.0) MECHANICAL :
 - 3.1. DURABILITY , MINIMUM: MATED 5000 CYCLES WITHOUT DEGRADING ELECTRICAL
 - 3.2. INITIAL-MATING FORCE: 300g~2000g UNMATING FORCE: 200g~2000g
 - 3.3. AFTER LIFE TESTING-MATING FORCE: 300g~2000g UNMATING FORCE: 200g~2000g

PRODUCT NO.

PJ05-06 A B 03-02

① ② ③ ④

① PRODUCT SERIES:

PJ05: PHONE JACK CONNECTOR

② PIN NO.:

06: 6P1N

③ MATERIAL:

A: LCP

④ SERIES NO.:

02:板上型,前两插后四插

YTCOON

Dongguan YTCOON
Electronics Technology Co., Ltd

CUSTOMER DRAWING

GENERAL TOLERANCE

X ±0.20

.XX ±0.15

.XXX ±0.10

ANGEL TOLERANCE

X ±5°

.XX ±2°

.XXX ±1°

DRAWING

DEV1

APPROVED

DATE

2014.06.23

UNIT

mm

SCALE

TITLE:

PHONE JACK CONNECTOR

P/N:

PJ05-06AB03-02

DRAWING NO.

C-PJ05-02

SIZE

A4

SHEET

1 of 1

REV

A

101

81