

SPECIFICATIONS

- 1.VOLTAGE RATING:30V AC
- 2.CURRENT RATING:WHEN APPLYING CURRENT ONLY TO SIGNAL TERMINALS:
 - 1.0A(FOR TERMINAL NO.2,3 AND 4)
 - WHEN APPLYING CURRENT ONLY TO POWER TERMINALS:
 - 1.8A(FOR TERMINAL NO.1 AND 5)
 - 0.5A(FOR TERMINAL NO.2,3 AND 4)
- 3.INSULATION RESISTANCE:100M MIN/AT 100V DC
- 4.DIELECTRIC WITHSTANDING VOLTAGE:100V(r.m.s)AC FOR 1 MINUTE
- 5.CONTACT RESISTANCE:30m MAX.
- 6.OPERATING TEMPERATURE:-30 TO +80?

PRODUCT NO.

MU13 - 05 A B 05 - 02

- ①
- ②
- ③
- ④

①产品系列:

MU13: MICRO USB 5PIN RECEPTACLE

② 产品PIN数:

05: 5PIN

③ 材质:


A: LCP

④ 产品流水号

02: 沉板0.8 DIP AB TYPE 无翻边

RECOMMEND P.C.B.LAYOUT

7		8		9		10	
REV	ECN #	DESCRIPTION	DRAWING	APPROVED	DATE		
A		NEW RELEASE	DEV1		2012/04/26		

CUSTOMER DRAWING									
YTCONN http://www.ytconn.com									
<i>Dongguan YTCONN Electronics Technology Co., Ltd.</i>									
GENERAL TOLERANCE			DRAWING		DEV1		TITLE: MI CRO USB 5PIN RECEPTACLE 沉板0.8 DIP AB TYPE 无翻边		
X ±0.20 .XX ±0.15 .XXX ±0.10			APPROVED		P/N:		MU13-05AB05-02		
ANGEL TOLERANCE X ±3° .XX ±2° .XXX ±1°			DATE		2013. 05. 11		DRAWING NO. C-MU13-02		
		UNIT		mm		SCALE		1:1	
		SIZE		A4		SHEET		1 of 1	
		REV		A					