



REV	EON #	DESCRIPTION	DRAWING	APPROVED	DATE
A		NEW RELEASE	DEYI		2012\12\07

NOTES:

- MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC FLAMMABILITY RATING UL94V-0
 - 1.2 CONTACT: COPPER ALLOY T=0.15mm
 - 1.3 SHELL: STAINLESS STEEL T=0.30mm
- FINISH:
 - 2.1 CONTACT:
 - 50' MIN. PLATED ON CONTACT AREA
 - G/F PLATING ON SOLDER TAIL AREA
 - 50~80' NICKEL UNDERPLATING OVERALL
 - 2.2 SHELL:
 - 80~120' WATER TIN PLATING ALL
 - 50~80' NICKEL UNDERPLATING OVERALL
- SPECIFICATION:
 - 3.1 CURRENT RATING: 0.5A(2.34CONTACT)/1.8A(1.5CONTACT) MAX.
 - 3.2 VOLTAGE: 30 VAC
 - 3.3 TEMPERATURE RANGE: -30 °C ~ 85 °C
 - 3.4 CONTACT RESISTANCE: 30 MILLIONHM MAX.
 - 3.5 DIELECTRIC WITHSTANDING VOLTAGE: 250 VAC r.m.s
 - 3.6 INSULATION RESISTANCE: 100 MEGOHMS MIN

PRODUCT NO.

MI08 - 05 A B 03 - 05

① ② ③ ④

① 产品系列:

MI08: MICRO USB 连接器

② 产品PIN数:

05: 5PIN

③ 材质:

A: LCP

④ 产品流水码:

05: 外壳前插后贴, 无翻边

CUSTOMER DRAWING

YTCOONN
 http://www.hnyycoon.com

Dongguan YTCOONN Electronics Technology Co., Ltd

GENERAL TOLERANCE	X	DRAWING	DEYI	TITLE:	MICRO USB 5P沉板0.8 前插后贴
	X ±0.20	APPROVED		P/N:	MI08-05AB03-05
	XX ±0.15	DATE	2015. 06. 22	DRAWING NO.	C-MI08-05
	XXX ±0.10	UNIT	mm	SCALE	1:1
ANGEL TOLERANCE	X ±3°	SIZE	A4	SHEET	1of1
	XX ±2°	REV			A
	XXX ±1°				