


RECOMMENDED PCB LAYOUT
 TOLERANCE:±0.05

TABLE A:

ITEM	P/N	DIM.A	REMARK	POST
00	BT15-03AB05-00	4.5H		有柱
01	BT15-03AB05-01	5.0H		有柱
02	BT15-03AB05-02	5.5H		有柱
03	BT15-03AB05-03	6.0H		有柱
04	BT15-03AB05-04	6.0H		无柱
05	BT15-03AB05-05	4.5H		无柱
08	BT15-03AB05-08	6.0H	端子镀铜	有柱



REV	ECN #	DESCRIPTION	DRAWING	APPROVED	DATE
A		NEW RELEASE	DE1		2012/4/24

- NOTES:
- MATERIAL
 - 1.1,HOUSING:THERMOPLASTIC,UL 94V-0 COLOR:BLACK
 - 1.2,CONTACT:COPPER ALLOY T=0.50
 - 1.3,CAP:THERMOPLASTIC,UL 94V-0 COLOR:BLACK
- 2.FINISH:
- 2.1,CONTACT:3U"GOLD PLATING ON CONTACT AREA
 - 80U"MIN NICKEL UNDERPLATING OVER ALL

PRODUCT NO. _____
 BT15-03 A B 05-XX
 ① ② ③ ④

- PRODUCT SERIES:
- BT15:电池连接器 4. 60H 3. 0pitch
 - PIN NO.:
 - 03: 3PIN
 - MATERIAL:

- A: LCP
- ④ SERIES NO.:
- 00: 3PIN 4. 5H 有柱
 - 01: 3PIN 5. 0H 有柱
 - 02: 3PIN 5. 5H 有柱
 - 03: 3PIN 6. 0H 有柱
 - 04: 3PIN 6. 0H 无柱
 - 05: 3PIN 4. 5H 无柱
 - 06: 3PIN 5. 4H 无柱
 - 07: 3PIN 5. 0H 无柱

ITEM	NAME	Q'TY/EACH	MATERIAL/FINISHED	REMARK
3	PAD	2	COPPER ALLOY SN PLATED	
2	CONTACT	3	COPPER ALLOY MATING AREA Au PLATED	
1	HOUSING	1	THERMOPLASTIC UL94V-0, BLACK	

CUSTOMER DRAWING

YTCOON
 http://www.hytcconn.com

Dongguan YTCOON Electronics Technology Co., Ltd.

GENERAL TOLERANCE	DRAWING	DEVI	TITLE:
X			3PIN 3. 0pitch 有柱 电池连接器
X ±0.20	APPROVED		P/N:
XX ±0.15			BT15-03AB05-0*
XXX ±0.10	DATE	2012. 04. 24	DRAWING NO. C-BT15-00
ANGEL TOLERANCE			
X ±3	UNIT	mm	SCALE
XX ±2	SCALE	1:1	SIZE A4
XXX ±1	SHEET	1 of 1	SHEET