



电烙焊图

REV	ECN #	DESCRIPTION	DRAWING	APPROVED	DATE
A		NEW RELEASE	DEY1		2012/04/26

- NOTES:
- CONTACT CURRENT RATING: 1A.
 - CONTACT RESISTANCE: 50 m² MAX.;
 - INSULATION RESISTANCE: 1000² MIN.;
 - DIELECTRIC WITHSTANDING: 500V AC MIN.;
 - DURABILITY: 5,000 CYCLES MIN.;
 - CONNECTOR MATING FORCES: 29.4N (3.00kgf) MAX.;
 - CONNECTOR UNMATING FORCES: 2.94N(0.30kgf) MIN.;
 - PRODUCT MEET THE REQUEST OF THE RoHS, SEE TABLE A:

PRODUCT NO.

PJ12-06 A B 05-00

- ① ② ③ ④

① PRODUCT SERIES:

PJ12:AUDIOD JACK 4.7H

② PIN NO.:

06: 6PIN

③ MATERIAL:

A: PA-9T

④ SERIES NO.:

00: 前四插后两贴

CUSTOMER DRAWING

YTCOON

Dongguan YTCOON Electronics Technology Co., Ltd

GENERAL TOLERANCE	DRAWING	DEV1	TITLE:	AUD10 JACK 4.7H 斜口, 板上型
X ±0.20	APPROVED		P/N:	前四插后两贴
.XX ±0.15	DATE	2016. 01. 12	DRAWING NO.	PJ12-06AB05-00
.XXX ±0.10	UNIT	mm	SCALE	1:1
ANGEL TOLERANCE	SIZE	A4	SHEET	10/2
X ±.5	REV	B		
.XX ±.2				
.XXX ±.1				

TABLE A:

ITEM	NAME	QTY	MATERIAL / FINISH
7	HOUSING	1	HIGH TEMPERATURE UL 94-V0 BLACK
6	CONTACT 6	1	COPPER ALLOY/CONTACT AREA GOLD PLATED
5	CONTACT 5	1	COPPER ALLOY/CONTACT AREA GOLD PLATED
4	CONTACT 4	1	COPPER ALLOY/CONTACT AREA GOLD PLATED
3	CONTACT 3	1	COPPER ALLOY/CONTACT AREA GOLD PLATED
2	CONTACT 2	1	COPPER ALLOY/CONTACT AREA GOLD PLATED
1	CONTACT 1	1	COPPER ALLOY/CONTACT AREA GOLD PLATED