

- NOTES:
- CONTACT CURRENT RATING: 1A.
  - CONTACT RESISTANCE: 50 m<sup>2</sup> MAX.;
  - INSULATION RESISTANCE: 1000<sup>2</sup> MIN.;
  - DIELECTRIC WITHSTANDING: 500V AC MIN.;
  - DURABILITY: 5,000 CYCLES MIN.;
  - CONNECTOR MATING FORCES: 29.4N (3.00Kgf) MAX.;
  - CONNECTOR UNMATING FORCES: 2.94N(0.30Kgf) MIN.;
  - PRODUCT MEET THE REQUEST OF THE ROHS, SEE TABLE A:

PRODUCT NO.

PJ08-06 A B 05-05

- ① ② ③ ④

① PRODUCT SERIES:

PJ08:PHONE JACK CONNECTOR slim 1.0mm type.

② PIN NO.:

04: 4PIN


06: 6PIN

③ MATERIAL:

A: PA9T

④ SERIES NO.:

05: L=13mm 短头前插后贴



( $\phi$ 3.50mm 4 POLE PLUG DETAIL DRAWING)

ITEM	PART NAME	QTY	MATERIAL	DESCRIPTION	REMARK
⑦	HOUSING	1	PPA	Gold Flash	Block
⑥	CONTACT F	1	PHOSPHOR BRONZE 0.20T	Gold Flash	
⑤	CONTACT E	1	PHOSPHOR BRONZE 0.20T	Gold Flash	
④	CONTACT D	1	PHOSPHOR BRONZE 0.20T	Gold Flash	
③	CONTACT C	1	PHOSPHOR BRONZE 0.20T	Gold Flash	
②	CONTACT B	1	PHOSPHOR BRONZE 0.20T	Gold Flash	
①	CONTACT A	1	PHOSPHOR BRONZE 0.20T	Gold Flash	

**CUSTOMER DRAWING**

**YTCONN**  
Dongguan YTCOON Electronics Technology Co., Ltd.

GENERAL TOLERANCE	DRAWING	DEVI	TITLE:	PHONE JACK CONNECTOR
X $\pm$ 0.20	APPROVED		slim 1.0mm type L=13mm	短头前插后贴
.XX $\pm$ 0.15	DATE	2012.04.26	P/N:	PJ08-06AB05-05
.XXX $\pm$ 0.10	UNIT	mm	DRAWING NO.	C-PJ08-05
ANGEL TOLERANCE	SCALE	1:1	SIZE	A4
X $\pm$ 5°	SHEET	1	SHEET	1
.XX $\pm$ 7°	REV		REV	A
.XXX $\pm$ 1°				